BUTYL ACETATE 99%

Page: 1

Compilation date: 28/11/2018

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: BUTYL ACETATE 99%

CAS number: 123-86-4
EINECS number: 204-658-1
Product code: GPS9456

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC21: Laboratory chemicals.

1.3. Details of the supplier of the safety data sheet

Company name: Atom Scientific Ltd

2b East Tame Business Park

Hyde

Manchester SK14 4GX

Tel: 0161 366 5123 **Fax:** 01704 337167

Email: technical@atomscientific.com

1.4. Emergency telephone number

Emergency tel: 07833453806

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226; STOT SE 3: H336

Classification under CHIP: -: R10; -: R66; -: R67

Most important adverse effects: Flammable liquid and vapour. May cause drowsiness or dizziness.

2.2. Label elements

Label elements under CLP:

Hazard statements: H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

Signal words: Warning

Hazard pictograms: GHS02: Flame

GHS07: Exclamation mark





BUTYL ACETATE 99%

Page: 2

Precautionary statements: P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P370+378: In case of fire: Use dry powder or dry sand for extinction.

2.3. Other hazards

Other hazards: This substance/mixture contains no components considered to be either persistent,

bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at

levels of 0.1% or higher.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.1. Substances

Chemical identity: BUTYL ACETATE 99%

CAS number: 123-86-4 **EINECS number:** 204-658-1

Contains: Molecular Formula: C6H12O2

Molecular Weight: 116.16 g/mol

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Consult a doctor.

Eye contact: Flush eyes with water as a precaution.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Wash

out mouth with water. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. If unconscious, check for

breathing and apply artificial respiration if necessary. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Inhalation: No data available.

Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: No data available.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Water spray. Alcohol resistant foam. Dry chemical powder. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Not applicable.

BUTYL ACETATE 99%

Page: 3

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure

adequate ventilation. Eliminate all sources of ignition. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Refer to section

8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Contain spillage, and then collect with an electrically protected vacuum cleaner or by

wet-brushing and place in container for disposal according to local regulations (see

section 13).

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid inhalation of vapour or mist. Keep away from sources of ignition - No

smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Containers which are

opened must be carefully resealed and kept upright to prevent leakage.

Suitable packaging: Not applicable.

7.3. Specific end use(s)

Specific end use(s): No special requirement.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL

BUTYL ACETATE 99%

Page: 4

EU 724 mg/m3 966 mg/m3	
------------------------	--

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Handle in accordance with good industrial hygiene and safety practice. Wash hands

before breaks and at the end of workday.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Splash contact

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Break through time: 30 min Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices.

Wash and dry hands.

Eye protection: Face-shield. Safety glasses. Use equipment for eye protection tested and approved

under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection: Impervious clothing. Flame retardant antistatic protective clothing. The type of protective

equipment must be selected according to the concentration and amount of the

dangerous substance at the specific workplace.

Environmental: Prevent from entering in public sewers or the immediate environment. Do not let product

enter drains.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Fruit-like.

Boiling point/range°C: 124 - 126 °C **Melting point/range°C:** -78 °C

Flammability limits %: lower: 1.7 upper: 7.6

Flash point°C: 23 °C - closed cup Part.coeff. n-octanol/water: log Pow: 2.3 at 25°C

Autoflammability°C: 415 °C at 1,013 hPa Vapour pressure: 20 hPa at 25 °C

Relative density: 0.88 g/cm3 at 25 °C pH: 6.2 at ca.5 g/l

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

BUTYL ACETATE 99%

Page: 5

10.1. Reactivity

Reactivity: No data available.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: No data available.

10.4. Conditions to avoid

Conditions to avoid: Heat. Flames. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong reducing agents. Strong bases.

10.6. Hazardous decomposition products

Haz. decomp. products: Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values:

Route	Species	Test	Value	Units
ORAL	RAT	LD50	10.760	mg/kg
INHALATION	RAT	4H LC50	> 21	mg/l
DERMAL	RBT	LD50	> 14,112	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
STOT-single exposure	-	Based on test data

Symptoms / routes of exposure

Skin contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Inhalation: No data available.

Delayed / immediate effects: No data available.

Other information: Not applicable.

Section 12: Ecological information

BUTYL ACETATE 99%

Page: 6

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
FISH	96H LC50	18	mg/l
DAPHNIA	48H EC50	44	mg/l
ALGAE	48H EC50	674.7	mg/l

12.2. Persistence and degradability

Persistence and degradability: Readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Harmful to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra

care in igniting as this material is highly flammable. Offer surplus and non-recyclable

solutions to a licensed disposal company.

Recovery operations: Not applicable.

Disposal of packaging: Dispose of as unused product.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1123

14.2. UN proper shipping name

Shipping name: ADR/RID: BUTYL ACETATES

IMDG: BUTYL ACETATES

IATA: Butyl acetates

BUTYL ACETATE 99%

Page: 7

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: 3

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: This safety datasheet complies with the requirements of Regulation (EC) No.

1907/2006.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

453/2010.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and 3: H226: Flammable liquid and vapour.

H336: May cause drowsiness or dizziness.

R10: Flammable.

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapours may cause drowsiness and dizziness.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.