DPX MOUNTANT STANDARD VISCOSITY

Page: 1

Compilation date: 09/01/2019

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: DPX MOUNTANT STANDARD VISCOSITY

Product code: RRSP29

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC21: Laboratory chemicals.

1.3. Details of the supplier of the safety data sheet

| Company name: | Atom Scientific Ltd |
|---------------|------------------------------|
| | 2b East Tame Business Park |
| | Hyde |
| | Manchester |
| | SK14 4GX |
| Tel: | 0161 366 5123 |
| Fax: | 01704 337167 |
| Email: | technical@atomscientific.com |

1.4. Emergency telephone number

Emergency tel: 07833453806

Section 2: Hazards identification

2.1. Classification of the substance or mixture

| Classification under CLP: | Skin Irrit. 2: H315; Acute Tox. 4: H312+332; Flam. Liq. 3: H226 |
|---------------------------------|--|
| Classification under CHIP: | -: R10; Xn: R20/21; Xi: R38 |
| Most important adverse effects: | Flammable liquid and vapour. Harmful in contact with skin or if inhaled. Causes skin |
| | irritation. |

2.2. Label elements

| Label elements under CLP: | | |
|---------------------------|---|--|
| Hazard statements: | H226: Flammable liquid and vapour. | |
| | H312+332: Harmful in contact with skin or if inhaled. | |
| | H315: Causes skin irritation. | |
| Signal words: | Warning | |
| Hazard pictograms: | GHS02: Flame | |
| | GHS07: Exclamation mark | |
| | | |



DPX MOUNTANT STANDARD VISCOSITY

| Precautionary statements: | P260: Do not breathe dust/fumes/gas/mist/vapours/spray. |
|---------------------------|---|
| | P280: Wear protective gloves/protective clothing/eye protection/face protection. |
| | P303+361+353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. |
| | Rinse skin with water/shower. |
| | P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position |
| | comfortable for breathing. |
| | P312: Call a POISON CENTER or doctor if you feel unwell. |
| | P370+378: In case of fire: Use suitable media for extinction. |
| | |

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

XYLENE

| EINECS | CAS | CHIP Classification | CLP Classification | Percent |
|-----------|-----------|---------------------|---|---------|
| 215-535-7 | 1330-20-7 | - | Flam. Liq. 3: H226; Acute Tox. 4: H332; | 70-90% |
| | | | Acute Tox. 4: H312; Skin Irrit. 2: H315 | |

| Section 4: First aid measures | | |
|-----------------------------------|---|--|
| 4.1. Description of first aid mea | asures | |
| Skin contact: | Remove all contaminated clothes and footwear immediately unless stuck to skin. | |
| | Drench the affected skin with running water for 10 minutes or longer if substance is still | |
| | on skin. Consult a doctor. | |
| Eye contact: | Bathe the eye with running water for 15 minutes. Consult a doctor. | |
| Ingestion: | Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water | |
| | to drink immediately. Consult a doctor. | |
| Inhalation: | Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a | |
| | doctor. | |
| 4.2. Most important symptoms | and effects, both acute and delayed | |
| Skin contact: | There may be irritation and redness at the site of contact. | |
| Eye contact: | There may be irritation and redness. The eyes may water profusely. | |
| Ingestion: | There may be soreness and redness of the mouth and throat. Nausea and stomach | |
| | pain may occur. There may be vomiting. | |
| Inhalation: | There may be irritation of the throat with a feeling of tightness in the chest. | |
| Delayed / immediate effects: | Immediate effects can be expected after short-term exposure. | |

Page: 2

DPX MOUNTANT STANDARD VISCOSITY

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol or polymer foam. Carbon dioxide. Dry chemical powder. Use water spray to cool

containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid. Eliminate all sources of ignition.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.Do not handle in a confined space. Avoid the formation or spread of mists in the air.Smoking is forbidden. Use non-sparking tools.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

DPX MOUNTANT STANDARD VISCOSITY

Page: 4

Suitable packaging: Not applicable.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

XYLENE

| Workplace ex | cposure limits: | | Respirable dust | |
|--------------|-----------------|--------------|-----------------|--------------|
| State | 8 hour TWA | 15 min. STEL | 8 hour TWA | 15 min. STEL |
| UK | 220 mg/m3 | 441 mg/m3 | - | - |

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

| Engineering measures: | Ensure there is sufficient ventilation of the area. Ensure lighting and electrical |
|-------------------------|--|
| | equipment are not a source of ignition. |
| Respiratory protection: | Self-contained breathing apparatus must be available in case of emergency. |
| Hand protection: | Impermeable gloves. |
| Eye protection: | Safety glasses. Ensure eye bath is to hand. |
| Skin protection: | Impermeable protective clothing. |
| Environmental: | Not applicable. |

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Flash point°C: 29

9.2. Other information

Other information: Not applicable.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

DPX MOUNTANT STANDARD VISCOSITY

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

XYLENE

| ORL | MUS | LD50 | 2119 | mg/kg |
|-----|-----|------|------|-------|
| ORL | RAT | LD50 | 4300 | mg/kg |
| SCU | RAT | LD50 | 1700 | mg/kg |

Relevant effects for mixture:

| Effect | Route | Basis |
|--------------------------|---------|-----------------------|
| Acute toxicity (harmful) | INH DRM | Hazardous: calculated |
| Irritation | DRM | Hazardous: calculated |

| Symptoms / | / routes o | f exposure |
|------------|------------|------------|
|------------|------------|------------|

 Skin contact:
 There may be irritation and redness at the site of contact.

 Eye contact:
 There may be irritation and redness. The eyes may water profusely.

 Ingestion:
 There may be soreness and redness of the mouth and throat. Nausea and stomach pain may occur. There may be vomiting.

 Inhalation:
 There may be irritation of the throat with a feeling of tightness in the chest.

 Delayed / immediate effects:
 Immediate effects can be expected after short-term exposure.

 Other information:
 Not applicable.

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

DPX MOUNTANT STANDARD VISCOSITY

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Recovery operations: Not applicable.

Disposal of packaging: Dispose of as unused product.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1993

14.2. UN proper shipping name

Shipping name: FLAMMABLE LIQUID, N.O.S.

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: This safety datasheet complies with the requirements of Regulation (EC) No.

1907/2006.

[cont...]

Marine pollutant: No

DPX MOUNTANT STANDARD VISCOSITY

15.2. Chemical Safety Assessment

| Chemical safety assessment: | A chemical safety assessment has not been carried out for the substance or the mixture |
|-----------------------------|--|
| | by the supplier. |

Section 16: Other information

| Other information | |
|----------------------------|--|
| Other information: | This safety data sheet is prepared in accordance with Commission Regulation (EU) No |
| | 453/2010. |
| | * indicates text in the SDS which has changed since the last revision. |
| Phrases used in s.2 and 3: | H226: Flammable liquid and vapour. |
| | H312: Harmful in contact with skin. |
| | H312+332: Harmful in contact with skin or if inhaled. |
| | H315: Causes skin irritation. |
| | H332: Harmful if inhaled. |
| | R10: Flammable. |
| | R20/21: Harmful by inhalation and in contact with skin. |
| | R38: Irritating to skin. |
| Legal disclaimer: | The above information is believed to be correct but does not purport to be all inclusive |
| | and shall be used only as a guide. This company shall not be held liable for any |
| | damage resulting from handling or from contact with the above product. |
| | |