TOLUENE 99.5% ACS

Page: 1

Compilation date: 23/10/2018

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: TOLUENE 99.5% ACS

CAS number: 108-88-3

EINECS number: 203-625-9

Product code: GPS1009

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC21: Laboratory chemicals.

1.3. Details of the supplier of the safety data sheet

Company name: Atom Scientific Ltd

2b East Tame Business Park Hyde Manchester SK14 4GX Tel: 0161 366 5123 Fax: 01704 337167

.

Email: technical@atomscientific.com

1.4. Emergency telephone number

Emergency tel: 07833453806

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP:	Flam. Liq. 2: H225; STOT SE 3: H336; Skin Irrit. 2: H315; Repr. 2: H361d; STOT RE 2:
	H373; Asp. Tox. 1: H304
Classification under CHIP:	F: R11; Xi: R38; Xn: R48/20; Xn: R63; Xn: R65; -: R67
Most important adverse effects:	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways.
	Causes skin irritation. May cause drowsiness or dizziness. Suspected of damaging the
	unborn child. May cause damage to organs through prolonged or repeated exposure.

2.2. Label elements

Label elements under CLP:

Hazard statements: H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H336: May cause drowsiness or dizziness.

H361d: Suspected of damaging the unborn child.

H373: May cause damage to organs through prolonged or repeated exposure.

TOLUENE 99.5% ACS

 Signal words:
 Danger

 Hazard pictograms:
 GHS02: Flame

 GHS07: Exclamation mark
 GHS08: Health hazard

 VVV
 VVV

 Precautionary statements:
 P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

 P260: Do not breathe dust/fumes/gas/mist/vapours/spray.
 P260: Wear protective gloves/protective clothing/eye protection/face protection.

 P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.
 P370+378: In case of fire: Use dry powder or dry sand for extinction.

 P403: Store in a well-ventilated place.
 P235: Keep cool.

Other hazards: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.1. Substances

Chemical identity: TOLUENE 99.5% ACS CAS number: 108-88-3 EINECS number: 203-625-9 Contains: Molecular Formula : C7H8 Molecular Weight : 92.14 g/mol

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Wash out mouth with water. Consult a doctor.

Inhalation: Move to fresh air in case of accidental inhalation of vapours. If unconscious, check for

breathing and apply artificial respiration if necessary. Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

TOLUENE 99.5% ACS

Ingestion: No data available.

Inhalation: No data available.

Delayed / immediate effects: May cause drowsiness or dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: No data available.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Water spray. Alcohol resistant foam. Dry chemical powder. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Not applicable.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

 Personal precautions:
 Use personal protective equipment. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Eliminate all sources of ignition. Evacuate the area immediately. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Refer to section 8 of SDS for personal protection details.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Contain spillage, and then collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13).

6.4. Reference to other sections

Reference to other sections: Refer to section 13 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid contact with skin and eyes. Avoid inhalation of vapour or mist. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.

For precautions see section 2.2.

TOLUENE 99.5% ACS

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in cool, well ventilated area. Containers which are opened must be carefully

resealed and kept upright to prevent leakage. Handle and store under inert gas.

Suitable packaging: Not applicable.

7.3. Specific end use(s)

Specific end use(s): No special requirement.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits:

State 8 hour TWA 15 min. STEL 8 hour TWA 15 min. STEL EU 192 mg/m3 384 mg/m3 191 mg/m3 384 mg/m3

Respirable dust

8.1. DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Handle in accordance with good industrial hygiene and safety practice. Wash hands
	before breaks and at the end of workday.
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.
Hand protection:	Full contact
	Material: Fluorinated rubber
	Minimum layer thickness: 0.7 mm
	Break through time: 480 min Splash contact
	Material: Fluorinated rubber
	Minimum layer thickness: 0.7 mm
	Break through time: 480 min
Eye protection:	Face-shield. Safety glasses.
Skin protection:	Complete suit protecting against chemicals. Flame retardant antistatic protective
	clothing. The type of protective equipment must be selected according to the
	concentration and amount of the dangerous substance at the specific workplace.
Environmental:	Do not let product enter drains. Prevent from entering in public sewers or the immediate
	environment.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:LiquidColour:ColourlessOdour:Aromatic

TOLUENE 99.5% ACS

Solubility in water: 0.5 g/l at 15 °C

Boiling point/range°C: 110-111

Flammability limits %: lower: 1.2

Flash point°C: 4

Melting point/range°C: -93 upper: 7

Autoflammability°C: 535

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: No data available.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: No data available.

10.4. Conditions to avoid

Conditions to avoid: Heat. Flames. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: Hazardous decomposition products formed under fire conditions. - Carbon oxides

Other decomposition products - No data available

In the event of fire: see section 5

Section 11: Toxicological information

11.1. Information on toxicological effects

Relevant hazards for substance:

Hazard	Route	Basis
Skin corrosion/irritation	DRM	Based on test data
Reproductive toxicity		Based on test data
STOT-single exposure	-	Based on test data
STOT-repeated exposure	-	Based on test data
Aspiration hazard	-	Based on test data

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: No data available.

TOLUENE 99.5% ACS

Inhalation: No data available.

Delayed / immediate effects: May cause drowsiness or dizziness.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

Species	Test	Value	Units
FISH	96H LC50	5.8	mg/l
DAPHNIA	48H EC50	6	mg/l
ALGAE	48H EC50	245	mg/l

12.2. Persistence and degradability

Persistence and degradability: Readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations:	Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra
	care in igniting as this material is highly flammable. Offer surplus and non-recyclable
	solutions to a licensed disposal company.
Recovery operations:	Not applicable.
Disposal of packaging:	Dispose of as unused product.
NB:	The user's attention is drawn to the possible existence of regional or national
	regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1294

14.2. UN proper shipping name

Shipping name: ADR/RID: TOLUENE IMDG: TOLUENE IATA: Toluene

TOLUENE 99.5% ACS

	Page:
14.3. Transport hazard class(es	5)
Transport class:	3
14.4. Packing group	
	2
Packing group:	2
14.5. Environmental hazards	
Environmentally hazardous:	No Marine pollutant: No
14.6. Special precautions for u	ser
Special precautions:	No special precautions.
Section 15: Regulatory information	ation
15.1 Safaty health and anyira	amontal regulations/legislation apositis for the substance or mixture
15.1. Safety, nealth and environ	nmental regulations/legislation specific for the substance or mixture
Specific regulations:	This safety datasheet complies with the requirements of Regulation (EC) No.
	1907/2006.
15.2. Chemical Safety Assessn	nent
Chemical safety assessment:	A chemical safety assessment has not been carried out for the substance or the mixture
	by the supplier.
Section 16: Other information	
Other information	
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and 3:	H225: Highly flammable liquid and vapour.
	H304: May be fatal if swallowed and enters airways.
	H315: Causes skin irritation.
	H336: May cause drowsiness or dizziness.
	H361d: Suspected of damaging the unborn child.
	H373: May cause damage to organs <or affected,="" all="" if="" known="" organs="" state=""> through</or>
	prolonged or repeated exposure <state conclusively="" exposure="" if="" is="" it="" of="" proven="" route="" th="" that<=""></state>
	no other routes of exposure cause the hazard>.
	R11: Highly flammable.
	R38: Irritating to skin.
	R48/20: Harmful: danger of serious damage to health by prolonged exposure through
	inhalation.
	R63: Possible risk of harm to the unborn child.
	R65: Harmful: may cause lung damage if swallowed.
	R67: Vapours may cause drowsiness and dizziness.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive

TOLUENE 99.5% ACS

and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.